

## Iosso Seam Sealer Fact Sheet

Iosso Seam Sealer protects most seams from leaking. Best for use on cotton, cotton blends, polyester and synthetic woven fabrics. Water repellency will vary with vinyl coated and vinyl laminated fabrics due to seam construction. It will not change the look or feel of the fabric.

\*Recommended uses: awnings, canopies, tents, tarps, boat covers, boat seats, umbrellas, camping gear, shoes and boots.

\*Will not cause yellowing, or change color, feel or breatheability of the fabric.

\*Is not flammable as petroleum based products are. Also, easily ships by either ground or air without any special tags.

\*Non-silicon, non-petroleum based distillate formula which will not attract dirt.

\*Directions for use: Fabric should be clean and thoroughly dry before application. For best results, apply sealer to both sides of fabric at seam. Using applicator bottle, push sponge down on fabric letting fluid soak through seam completely. Allow fabric to dry for 24 hours before exposing to water. A second application may be applied. Seam Sealer should be re-applied whenever fabric is washed or has weathered.

\*For large areas – solution may be applied with an applicator sprayer. If spraying – use a pump type sprayer or sprayer with pressure less than 30psi.

\*One 4 oz bottle will cover approximately 50 feet of ½” seam. One gallon will cover approximately 50 feet of ½” seam. One gallon will cover approximately 150 square feet, or 1800 feet of ½” seam.

\*Available in a 4 oz bottle with dabber, 1 gallon, 5 gallon and larger